

Multi-Core Cable Fan-out Jumper and Pigtail

ACCELINK TECHNOLOGIES CO.,LTD.



Multi-Core Cable Fan-out Jumper and Pigtail fan out multi-core (4, 6, 8, 12 cores) cable to individual fibers jumper with connector endface to realize connection between multi-core cables, it is convenient and stable for connection.

Features

- Low insertion loss, high return loss
- Good repeatability, excellent interchangeability

Applications

- In-door connection
- High dense ODF and in-box connection of frame

Specifications

Parameter	Unit	Value											
		FC/PC	FC/UPC	FC/APC	SC/PC	SC/UPC	SC/APC	ST/PC	ST/UPC	ST/APC	MU/PC	LC/PC	LC/APC
Type													
Insertion loss	dB	Single mode: ≤ 0.3 , Multi-mode: ≤ 0.2											
Repeatability	dB	≤ 0.1											
Interchangeability	dB	≤ 0.2											
Return loss(SM fiber)	dB	≥ 50	≥ 50	≥ 60	≥ 50	≥ 50	≥ 60	≥ 50	≥ 50	≥ 60	≥ 50	≥ 50	≥ 60
Return loss(MM fiber)	dB	≥ 36 (no APC connector)											
Connection durability	times	> 1000											
Operation temperature	$^{\circ}\text{C}$	-25~+70			-40~+80			-40~+80			-40~+75		

Ordering information

M — <input type="text"/> — <input type="text"/> / <input type="text"/> — <input type="text"/> / <input type="text"/> — <input type="text"/> — <input type="text"/> — <input type="text"/> — <input type="text"/>									
4:4 cores 6:6 cores 8:8 cores 12:12 cores	FC, SC, ST, MU, LC	PC, UPC, APC	o:Pigtail FC, SC, ST, MU, LC	o:Pigtail PC, UPC, APC	S:G.652 M:50/125 D:62.5/125	07:0.7m customer specify	09: Φ 0.9mm 20: Φ 2.0mm	5:5m customer specify	
Core number	Connector of the first end	End type of the first ferrul	Connector of the second end	End type of the second ferrul	Fiber type	Fan-outed length	Fiber Dia.	Fiber length	