

C-Band Erbium Fiber Wavelength TFL series

2006-08-24 - v1.0

Applications: Instrument for R&D labs and components testing
Form factor: Benchtop 19" Rackable
product reference: KPS-STD-BT-TFL-1550-LC-03-xxx-yy-zz



Optical Specifications:

Conditions	Unit	LC-01	LC-02	LC-03	LC-05	LC-10	LC-20	LC-50	LC-100	
Mode of operation		CW								
Nominal output power	<i>W</i>	0,1	0,2	0,3	0,5	1	2	5	10	
Central wavelength.	vaccum <i>nm</i>	min: 1535 max: 1565								
Input/Interstage isolation		Yes								
Output isolation		Yes							No	
Output monitoring		Yes							No	
Piezzo tuning		No								
Wl. Tunability	<i>nm</i>	MEC min: 30								
Control Mode		ACC, APC							ACC	
APC Pw. Tunability	%	55-100							-	
APC Pw. Stability	8h, 25°C <i>%rms</i>	max: 3							-	
Linewidth	FWHM <i>nm</i>	max: 1								
M²	LP01	max: 1.1								

Optical Interface:

	LC-01	LC-02	LC-03	LC-05	LC-10	LC-20	LC-50	LC-100	
Output termination options	FA, SA, FP, SP		FA, SA, FP, SP, Col, E2PS, B				Col, E2PS, B		
Output pigtail	SMF28, Front-panel		SMF28, 3mm, PVC, 1m						
Backreflection	-		Limited						
Injected linewidth	Limited								

Electrical, Environmental and Packaging:

Electrical Specification:	Unit	BT
AC Voltage	<i>V</i>	85 to 264 VAC, 47-63Hz
Power Consumption	<i>W</i>	<200
Interface		RS232 and GPIB
Environmental		
Operating Temperature	°C	From 15 to 35
Storage Temperature	°C	From -20 to 55
Warm up time	<i>min</i>	<30
Dimension and Weight		
Dimensions Laser module	<i>mm</i>	88x448x446
Weight	<i>Kg</i>	<5

Options available:

- xxx = IN monitoring or PZT, ISO, APC / OUT monitoring options (see specifications)
- yy = non available
- zz = output termination option

Connectors:

FA=FC/APC; SA=SC/APC; FP=FC/SPC; SP=SC/SPC
E2PS=E2000 HP + Patchcord for adaptation
Col=Collimated, for free-space use; B=Bare Fiber

All products comply with IEC 60825-1 and FDA (21 CFR Subchapter J) laser safety standards.

Keopsys undertakes a continuous and intensive product development program to ensure that its products perform to the highest technical standards. As a result, the specifications in this document are subject to change without notice.



HEADQUARTERS
KEOPSYS SA.
21 rue Louis de Broglie
22300 Lannion, France
Tel: +33 2 9605 0800
Fax: +33 2 9605 0801

US OPERATIONS
KEOPSYS Inc.
16 White Bridge Road
Pittstown, NJ 08867, USA
Tel: +1 (908) 238-0898
Fax: +1 (908) 238-9178

websales@keopsys.com
www.keopsys.com

KEOPSYS
KEY OPTICAL SYSTEMS