

PM Ytterbium Fiber Amplifier

PM-YFA series

Applications: Instrument for R&D labs
 Form factor: Benchtop 19" Rackable
 product reference: KPS-STD-BT-YFA-30-PM-xxx-yy-zz



Optical Specifications:

	Conditions	Unit	YFA-10	YFA-20	YFA-30	YFA-40	YFA-50	YFA-100
Mode of operation			CW					
Nominal output power	Pin = +5dBm	W	1	2	3	4	5	10
Input power		dBm	From +5 to +15					
Bandwidth		nm	1050-1080					
Input/Interstage isolation			Yes					
Output isolation			Option	No				
Input monitoring			Option					
Output monitoring			No					
Control Mode			ACC					
PER	signal only	dB	min: 17			min: 15		
M²	LP01		max: 1.1					

Optical Interface:

	YFA-10	YFA-20	YFA-30	YFA-40	YFA-50	YFA-100
Output termination options	FA, Col, B	Col, B				
Output pigtail	Panda980, 3mm, PVC, 1m					
Input termination options	FA					
Input pigtail	Panda980, 3mm, PVC, 1m					
External fiber restriction	-	No connexion				
Backreflection	Limited					
Injected linewidth	Limited					

Electrical, Environmental and Packaging:

		Unit	BT
Electrical Specification:			
	AC Voltage	V	85 to 264 VAC, 47-63Hz
	Power Consumption	W	<400
	Interface		RS232 and GPIB
Environmental			
	Operating Temperature	°C	From 15 to 35
	Storage Temperature	°C	From -20 to 55
	Warm up time	min	<30
Dimension and Weight			
	Dimensions Laser module	mm	88x448x446
	Weight	Kg	<5

Options available:

- xxx = IN monitoring, ISO, APC / OUT monitoring options (see specifications)
- yy = input termination option
- zz = output termination option

Connectors:

FA=FC/APC; SA=SC/APC; FP=FC/SPC; SP=SC/SPC
 E2PS=E2000 HP + Patchcord for adaptation
 Col=Collimated, for free-space use; B=Bare Fiber

All products comply with IEC 60825-1 and FDA (21 CFR Subchapter J) laser safety standards.
 Keopsys undertakes a continuous and intensive product development program to ensure that its products perform to the highest technical standards. As a result, the specifications in this document are subject to change without notice.



HEADQUARTERS
 KEOPSYS SA.
 21 rue Louis de Broglie
 22300 Lannion, France
 Tel: +33 2 9605 0800
 Fax: +33 2 9605 0801

US OPERATIONS
 KEOPSYS Inc.
 16 White Bridge Road
 Pittstown, NJ 08867, USA
 Tel: +1 (908) 238-0898
 Fax: +1 (908) 238-9178

websales@keopsys.com
www.keopsys.com

