

Coarse Wavelength Division Multiplexer – CWDM mux or demux, 4 channels

Features

- Devices may be used as multiplexer or demultiplexer
- Upgrade channel, integrated bandsplitters and tap ports available
- Micro-hybrid construction in a sealed metal housing
- Epoxy-free optical path
- Extremely small component dimensions: 19 x 15.5 x 9 mm³, other dimensions on request
- Flexible Location of Fiber Ports, for details see Products page
- Also available as integrated Patch Cord CWDM for flexible system configurations to enable multiplexing without using any board space
- Single mode and multi mode fibers possible, fiber packaging: loose tube or 250 µm coating

Applications

- Combines / separates up to 4 channels with a 20 nm spacing
- Metro Core, Metro Access, Metro Enterprise, Cable TV, 3G Telephony (UMTS), Datacom, WAN, RFTS, Sensor Applications
- Analog and digital transmission systems

Specifications

Parameters	Coarse Wavelength Division Multiplexer – mux/demux (all values refer to single mode)		
Channels	4, 4+ upgrade		
Center Wavelength [nm]	choice of 4 wavelengths within <u>one</u> band		
Band 1 (red band)	1471 / 1491 / 1511 / 1531 / 1551 / 1571 / 1591 / 1611		
Band 2 (blue band)	1271 / 1291 / 1311 / 1331 / 1351 / 1371 / 1391 / 1411 / 1431 / 1451		
	Upgrade: remaining wavelengths of band other wavelength upon request; please contact CUBO		
Optical Bandwidth	> 13 nm (higher bandwidth on request)		
Insertion Loss *	4 channel CWDM	Standard < 1.9 dB	Premium < 1.7 dB
	4+ upgrade channel CWDM	Standard < 2.0 dB	Premium < 1.8 dB
Isolation **	adjacent channel	> 30 dB	
	non-adjacent channel	> 40 dB	
	Isolation Spectral Range Band 1 (red)	1460-1620 nm	
	Isolation Spectral Range Band 2 (blue)	1260-1460 nm	
Return Loss *	> 45 dB (50 dB typ.)		
Directivity	> 50 dB		
Polarization Dependent Loss	< 0.2 dB		
Max. optical power	250 mW		
Operating Temperature	0°C to 70°C (-40°C to 85°C on request)		
Storage Temperature	-40°C to 85°C (when removed from plastic package)		
Package Dimensions	19 x 15.5 x 9 mm ³		

* With passband, valid over full temperature range and at all states of polarization but without connector losses.

** Valid over full temperature range and at all wavelengths across the channel.



光貿易株式会社

〒113-0034 東京都文京区湯島3-13-8湯島不二ビル301

TEL:03-3832-3117 FAX:03-3832-3118

Email: t.ito@hikari-trading.com

